Overhead stirrer “SE-100”


FOR BLENDS, HOMOGENIZATIONS, SUSPENSIONS, SOLUTIONS GASIFICATION AND SUBSTANCES RECIRCULATION. DESIGNED FOR CONTINUOUS WORK.
BRUSHLESS MOTORS FREE OF MAINTENANCE AND SPARKS.
PARTIALLY SEALED ENCAPSULATED CASES AGAINST SUBSTANCES AND AGRESSIVE VAPOURS.
THERMAL PROTECTION FOR OVERHEATING WITH AUTO POWER OFF AND LED INDICATOR.

FEATURES

Excellent blending results in an accurate and repeatable control.
Stirring by electronic control of speed, **from 60 to 2000 rpm.**
Specially designed for those samples in which its viscosity changes during the process.
Max stirring volume: **Up to 40 L** (in H20)
Max stirring viscosity: **Up to 1.000.000 mPas.**
Speed digital reading and pre-selection (rpm).
Adaptable spindle to stirring rods up to 9.5 mmØ.



OVERHEAD STIRRER ACCESSORIES



STIRRING SHAFTS WITH ROTORS

Shaft with AISI 304 stainless steel rotor. Shaft: 7mm Ø.

Part No.	Rotor type	Ø shaft mm	Total length mm	Features
6002891	1	90	400	Double fly vane
6002892	2	60	400	Fly vane
6002893	3	50	400	Fixed blade
6002894	4	50	400	Double cross vane
6002895	5	58	400	Helix
6002896	6	70	450	Six hole paddle
6002897	7	70	450	Three hole paddle
5050921	8	46	400	Radial turbine
5050932	9	45	400	Turbo helix 45 mm Ø
5050933	10	66	400	Turbo helix 66 mm Ø

MODEL

Part No.	Height/Width/Depth (external) cm	Power W	Weight Kg
7000385	17,5 7,5 13,5	100	2,8

Base and shaft not included.



Bosshead “MAXIM”
For large diameters.
Chrome plated with one opening to hold rods up to 30 mm Ø. Second opening up to 20 mm Ø.
Part No. 7000408



Double base support T “MAXI”
Rod of AISI 304 stainless steel of 20 Ø x 800 mm high.
Designed to support weights up to 20 Kg at 300 mm
height from the base. Useful for stirrers.
Weight: 7 Kg.
Part No. 6000410