Automatic bag sealer with printer “Seal-Com 3”

ACCORDING DIN 58953 SECTION 7 STANDARD. FOR SEALING STERILE PAPER, POLYPROPYLENE-POLYESTER BAGS. SPECIAL FOR A LARGE AMOUNT OF BAGS SEALING.

FEATURES

Exterior made from AISI 304 stainless steel, ideal for sealing plastic paper bags, solid plastic paper and only paper bags.
Heating time: 4 minutes.
Seal width: 12 mm.
Sealing speed: 10 m/min.
Acoustic sign of cycle starting.
Temperature touch control from 60 to 220ºC.



CONTROL PANEL

LCD touch screen 7” indicating:
- Setpoint temperature and actual temperature.
- Date and time (automatic date change).
- Print size.

PRINTING

Print sterilization date, expiration date, sterilization lot, name of the operator, name of the item and department.



MODEL

Part No.	Height / Width / Depth (sealer) cm	Power W	Weight Kg
4100049	22 56 26	500	20

ACCESSORIES

Roller table
Measures cm: 74.5 width x 28.6 depth x 5.2 height.
Part No. 4100053



SEALING MACHINE ACCESSORIES

Rolls of paper for sterilization “Polisteril”
Paper base polypropylene and polyester bags showing differing ink prints of sterilized items.

Part No.	Bag width cm	Bag length m
4100075	7,5	100
4100100	10	100
4100200	20	100



Sterile paper “Policort” trimmer
Completely made of metal with back and reel support, for a capacity of 2 x 200mm or 4 x 100 mm wide reels.
Circular cutting knife edge.
Measurements: 13 high x 51 wide x 32 cm deep.
Weight: 2.8 Kg.
Part No. 4100045



OPTIONS: **Ultrasonic cleaning** baths for dentistry, “Ultrasons-Digit”. **Dry sterilizer** “DRYTIME” poupinel oven (see page 143).