Platelet bags incubated cabinets “Blood Bank” E and F

EXCLUSIVE DESIGN ADAPTED TO ACCOMODATE PLATELET BAGS STIRRERS “APL”.
FORCED AIR CIRCULATION.
FIXED TEMPERATURE AT +22 °C. STABILITY ±1,5 °C. RESOLUTION 1 °C.
SEVEN DAYS GRAPHIC TEMPERATURE REGISTER.

SAFETY:
LOW TEMPERATURE THERMOSTAT LIMITER.
VISUAL AND ACOUSTIC INDICATORS: EXCESSIVE LOW TEMPERATURE (+18 °C), EXCESSIVE HIGH TEMPERATURE (+24 °C), OPEN DOOR, MAINS FAILURE TEMPERATURE GRAPHIC REGISTER. 7 DAYS RECORDER, AUTONOMY 6 MONTHS.
ACOUSTIC ALARM ON ALL FAIL CONDITIONS. ACOUSTIC INDICATOR.



Model E



Model F

APPLICATIONS

Storage cabinet specially designed for platelet bags preservation.

COMMON FEATURES

AISI 304 stainless steel external cabinet and internal lining.
Double glazed door, reversible lockable door, easy to change, with automatic feed-back mechanism and manual locking.
Hermetically sealed compressor mounted on antivibration settlement with forced type evaporator and ventilated type condenser.
Shelves and supports in steel PVC laminated.
2 power outlet base for model “Blood-Bank E” max. power 500 W
6 power outlet base for model “Blood-Bank F” max. power 500 W
Inner air circulation for a more temperature homogeneity.
Temperature sensors located in similar conditions to platelet bags.
Circular graphic register built-in.
Microprocessor temperature control that allows configuration and visualization of the following parameters by means of the display:
- **SET adjustment.**
- **Alarm adjustment.**
- **Calibration.**



Graphic recorder

OPTIONAL COMPLEMENTS

ETHERNET thermometer module
Temperature Record, with control of programmable warnings and graphic representation. It must be installed at the factory.
ETHERNET connection is needed at the place of use.
Part No: 2101627

Data logger with digital display
PT100 type probe with two meters of cable. Measuring range of -100 ºC. at +200 ° C. With GSM module for data transmission.
Part No. 2101520

SPARE PARTS

For 2101511. Part No. 1001862 Additional tray.
For 2101513. Part No. 1001863 Set 2 trays + additional central guide

MODELS	Part No.	Capacity litres	Capacity stirrers	Height / Width / Depth (interior) cm	Height / Width / Depth (exterior) cm	Power W	Power HP	Number of shelves	Weight Kg
Blood Bank E	2101511	560	2 x APL-54	153 54 66	213 80 79	497	3/8	4	165
Blood Bank F	2101513	1240	4xAPL-54 o 2xAPL-108	153 124 68	213 139 79	1034	5/8	8	212

They are supplied with trays and wheels.